

HIGH QUALITY, LCD MONITOR HEAD

KME has developed this display module for industrial applications where an economically priced SXGA TFT flat panel monitor is required with a bright screen and wide viewing angles. The unit is constructed from painted aluminium and incorporates triple data input including PAL/NTSC, enabling applications in security surveillance and machine vision to be addressed.

Automatic mode detection and picture scaling circuitry allow the display of resolutions lower than the 1280 x 1024 pixels native resolution.

The 29LM171A68MP/5 series is supplied with non-glare toughened glass protection screens as standard or no additional glass for those demanding SXGA applications where ultimate clarity is necessary.

SOLUTIONS FOR MONITOR HEADS

- > **Vesa standard fixings for ergo arm**
VESA fixings at the rear making it easy for wall mounting or use with ergo arms.
- > **Optional touch screen facility**
A touch screen can be integrated into the monitor
- > **Inputs**
All monitors have RCA and 15-D connectors, DVI-D
- > **Rugged metal construction with good stability**
The LCD monitor has been designed with solidity, being housed in a compact metal construction with a toughened glass protection screen.
- > Rear mounted Controls



17.0" LCD HEAD MONITOR

29LM171A68MP/5

DATASHEET

Electrical Description		Mechanical Description	
TFT Characteristics:	Type:	a-si TFT active matrix	Input: RCA, 15-D
	Max Resolution:	1280 x 1024 pixels	Housing: Painted aluminium
	Active Display Area:	337.9 x 270.3mm	User Controls: Rear mounted
	Response Time:	25ms average, typical	On Screen buttons: Standby, Brightness, Contrast, OSD
	Contrast Ratio:	450:1 typical	
	Brightness:	250cd/m ² typical	
	Viewing Angles (at CR>10):	160 ° / 160 °	
	Backlight Life:	50,000 hours typical	
	No. Colours:	16 Million	
	Video Signal:	PAL / NTSC Analog 0.7Vp-p	
Signal Sync:	Composite (CVBS) 1V p-p Separate H&V (+/-ve) TTL Sync-on-Green -0.3Vp-p		
Synchronisation Range:	Horizontal scan:	30kHz - 80kHz 15kHz (Pal / NTSC)	
	Vertical scan:	50 to 80Hz	
Display modes:	VESA Support:	640 x 480 VGA 800 X 600 SVGA 1024 x 768 XGA 1280 x 1024 (recommended)	
Power Supply:	90 - 260V AC 50/60Hz via integral power supply		
Power Consumption:	60W (Max)		
Environmental:	Storage Temp:	-20 to 65°C	Part Numbers: Model number: 29LM171A68MP/5
	Operating Temp:	0 to 50°C	Resistive touch screen via RS232: 29LM171AR68MP/5 (or USB option)

Due to a policy of continuous product development KME reserves the right to change specifications and descriptions without prior notification. All trademarks acknowledged.

KENT MODULAR ELECTRONICS LTD
 621 Maidstone Road
 Rochester, Kent ME1 3QJ
 T: +44 (0)1634 830123 F: +44 (0)1634 830619
 E: sales@kme.co.uk W: www.kme.co.uk



17.0" LCD HEAD MONITOR


29LM171A68MP/5

DATASHEET


FRONT VIEW




SIDE VIEW



REAR VIEW



BOTTOM VIEW



* Where Fitted

All dimensions in millimetres
(Not to scale)

KENT MODULAR ELECTRONICS LTD
621 Maidstone Road
Rochester, Kent ME1 3QJ
T: +44 (0)1634 830123 F: +44 (0)1634 830619
E: sales@kme.co.uk W: www.kme.co.uk

