

15" LCD MARINE RACKMOUNT MONITOR

29LR153A35PC/1

DATASHEET

Electrical Description		Mechanical Description	
TFT Characteristics:		Dimensions:	Monitor: 380 X 440 X 108 mm Weight: 3kg
Type:	15" a-Si TFT active matrix		
Max Resolution:	1024 x 768 pixels		
Active Display Area:	304.1 x 228.1mm		
Response Time:	20ms	Housing:	Aluminium
*Contrast Ratio:	450:1 typical	Sealing:	IP65 on front
*Brightness:	250cd/m ² typical	Approvals	
Viewing Angles (at CR>10):	130° / 130°	ECDIS & Radar Compliance:	
Backlight Life:	50,000 typical	IEC 61174:	Designed to comply
Power Supply:	110-230V AC 50-60Hz	EMC & Safety:	
Power Consumption:	50W (Max)		
Environmental:	**Operating Temp: 0 to +50 °C Storage Temp: -20 to +60 °C Operating Humidity: 50% to 90% (non condensing) Storage Humidity: 28% to 90% (non condensing)		
Panel PC features:		EN 60950	Designed to comply
1.5GHZ intel pentium processor, 1GB ram and 32GB compact flash or SATA drive		Marine Communications:	
Rear control connectors:	4 x USB, Parallel port, serial port, LAN, VGA output, PS2 keyboard, PS2 mouse	IEC 60945:	Designed to comply
Front inputs:	2 x USB		
		Part Numbers:	
		Monitor:	29LR153A35PC/1
**Quoted EN60945 test. We do not recommend routine operation at extreme temperatures * Brightness and Contrast refer to naked LCD panel			

Due to a policy of continuous product development KME reserves the right to change specifications and descriptions without prior notification. All trademarks acknowledged.

KENT MODULAR ELECTRONICS LTD
621 Maidstone Road
Rochester, Kent ME1 3QJ
T: +44 (0)1634 830123 F: +44 (0)1634 830619
E: sales@kme.co.uk W: www.kme.co.uk

