

17" RACKMOUNT MILITARY MONITOR

29LR173A35MP-M

DATASHEET

HIGH QUALITY, RUGGED MILITARY DISPLAY

The 29LR173A35MP-M Series of LCD monitors has been designed for industrial applications that require a compact VGA/SVGA compatible monitor with good viewability. It is constructed from painted aluminium, making it lightweight with good rigidity.

The 29LR173A35MP-M Series incorporates rugged chassis construction for shock and vibration. With wide viewing angles and deep dimming capabilities, this series of monitors is ideal for the more demanding of applications. The 35MP-M series has been designed to comply with military standards for shock & vibration and EMC.

SOLUTIONS FOR THE MILITARY ENVIRONMENT

- > Designed to comply with MIL-STD Shock, Vibration and EMC
- > Advanced Deep Dimming 2000:1
- > Contrast Enhancing AR Safety Glass
- > VGA – XGA & PAL/NTSC



17" RACKMOUNT MILITARY MONITOR

29LR173A35MP-M

DATASHEET

Electrical Description		Mechanical Description	
TFT Characteristics:		Dimensions:	Monitor: 440 x 352 x TBD (approx)
Type:	AM Colour TFT		
Max Resolution:	1280 x 1024 pixels	Housing	Aluminium
Active Display Area:	337.9 x 270.3mm		
Response Time:	10ms average, typical		
Contrast Ratio:	1000:1 typical @ CR≥10	Environment	
Brightness:	250cd/m ² typical	Operating Temp:	-10°C to +50°C
Viewing Angles (at CR>10):	178 ° / 178 °	Storage Temp:	-20°C to 60°C
No. Colours:	16 million	Sealing:	IP65min
		Operating Humidity:	50% to 90% (non condensing)
Connector:	Power: 851-02R123P50 Signal: 8STO-12G35SN	Storage Humidity:	28% to 90% (non condensing)
Synchronisation Range:			
Horizontal scan:	15kHz (PAL) - 91kHz	Shock:	Mil-STD-810F
Vertical scan:	56 - 85Hz	Vibration:	Mil-STD-461E
Display Modes:	1280 x 1024 SXGA (recommended) 1024 x 768 XGA 800 x 600 SVGA 640 x 480 VGA		
Power Supply:	90 - 260V AC 50/60Hz		
Power Consumption:	60W (Max)	Part Numbers:	
		Model number:	29LR173A35MP-M
		DC Monitor:	29LR173D35MP-M
		AC Touchscreen (resistive):	29LR173AR35MP-M
		DC Touchscreen (resistive):	29LR173DR35MP-M

Due to a policy of continuous product development KME reserves the right to change specifications and descriptions without prior notification. All trademarks acknowledged.